

M5900

Etiquetadora industrial de alta velocidad



Varios Idiomas



Memoria Superior



Bajo coste



Robustez en los mecanismos



Conectividad asegurada



Impresion directa no requiere ribbon



PRINTING SPECIFICATION		
Printing Method	Direct Thermal	
Print Resolution, dots/mm (dpi)	8 dots/mm (203dpi)	
Max. Print Area	Width, mm (inch)	112 mm (4.4")
	Pitch, mm (inch)	1249 mm (49.2")
Print Speed, mm/sec (ips)*	Up to 150 mm/sec (6ips)	
CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)		
Sensor Type	Reflective sensor for use with pre-printed marks Adjustable see through sensor for die-cut label with gap	
Media Type	Roll die-cut label with gap or pre-printed label, plain paper stock, tag stock continue stock	
Media Size (with backing paper size)	Width, mm	Label: 37 ~ 128 mm (Label with backing paper: 40 ~ 131 mm)
	Length, mm	Label: 25 ~ 356 mm (Label with backing paper: 28 ~ 359 mm)
	Thickness, mm	0.08 ~ 0.21 mm
Media Roll Size	Max. External Diameter, mm*	Ø 152 mm
	Inner Diameter, mm*	40 mm / 76.2 mm (core)
FONT / SYMBOLOGIES		
Font	Internal	XU, XS, XM, XB, XL, OCR-A/B / Outline fonts / CGTimes, CGTriumvirate
	Downloadable	TrueType Font
Barcode symbologies	1-Dimension	EAN 8/13, UPC - A/E, NW -7, POSTNET, Inter-leaved 2 of 5 (ITF), CODE 39, CODE 93, CODE 128, Bookland
	2-Dimension	PDF417 (ver 2.4), QR Code (ver 8.1), Maxi Code (ver 3.0) and Data Matrix code (ECC 200) ver 2.0, Veri Code
INTERFACE CHARACTERISTICS		
Processor	32-bit RISC	
Optional interface	Serial: RS-232C; Parallel: IEEE 1284, Centronics; LAN: 10/100BaseT, WLAN: IEEE 802.11b; USB; RS-422/485	
OPERATING CHARACTERISTICS		
Power Requirements	AC Voltage: 115/230 ±10%, Power consumption: peak 150W (Standby 20W)	
Environment	Operating	-5 ~ 40°C / 30 ~ 80% RH (w/out condensation)
	Storage	-5 ~ 60°C / 30 ~ 90% RH (w/out condensation)
Dimension (W x D x H), weight	W261 x D322 x H285 mm / 10.3kg	
OPTIONAL ACCESSORIES		
Cutter, dispenser, expansion memory, PCMCIA add-on memory		
OTHERS		
Function	Useful Features	Hex Dump, Print Custom Character Design, Graphic, Sequential Numbering for Number and Barcode, Form Storage and Recall for Faster Data Retrieving of Complex Formats.
	Self Diagnosis Checking	Head Check, Paper End Detection, Ribbon Near-End/End Detection (remaining 15m-30m detection), Open Cutter-Cover Detention, Auto Sensing for Continuous Forms, Memory Card Error Detection, Test Print.
	Operational Panel	16 x 2 line Alphanumeric. Two buttons: LINE, FEED.
	DIP Adjustment	Print Position Adjustment, Cutting/Tear-off Position Adjustment, Print Darkness Adjustment, LCD Contrast Adjustment.

* Measurements are approximate values



CONTACTO

🏠 c/Herminio Puertas, 14 - 28011 - Madrid - España

☎ +34 639 827 413

☎ +34 91 526 60 38

☎ +34 91 526 60 38

✉ info@v10consumibles.com

🌐 <http://www.v10consumibles.com>